

Acetylene Hose

乙炔管

Application : For acetylene welding /cutting service or general industry

Construction

Tube: SBR
Cover: Synthetic rubber, red , yellow color or corrugated surface are available

Reinforcement: Multiple textile braid

Temp.Range: -30 °C to + 70°C

Burst Pressure(B.P.): Working Pressure(W.P.) x 4

用途

乙炔氣焊接/切割用設備配管

構造

內管層: 苯乙烯丁二烯合成橡膠配方

外管層: 耐磨耗, 耐候性佳之特殊橡膠, 可另為溝紋, 或紅色, 黃色

補強層: 適合夾合之纖維編織補強

適用溫度: -30 °C 到 +70°C

爆破壓力: 為最高使用壓力的4倍

產品編號 part no.	I.D. 內徑		braid 編織	O.D. 成品外徑		W.P. 最高使用壓力		Length 長度 M 公尺
	inch	mm		inch	mm	psi	kgf/cm ²	
AT 0151	3/16	4.8	1	0.452	11.5	150	11	100
AT 0201	1/4	6.3	1	0.511	13.0	150	11	100
AT 0251	5/16	7.9	1	0.590	15.0	150	11	100
AT 0301	3/8	9.5	1	0.669	17.0	150	11	100

Oxygen Hose

氧氣管

Application : For oxygen welding/cutting service or general industry.

Construction

Tube: SBR
Cover: Synthetic rubber, red , yellow color or corrugated surface are available

Reinforcement: Multiple textile braid

Temp.Range: -30 °C to + 70°C

Burst Pressure(B.P.): Working Pressure(W.P.) x 4

用途

氧氣焊接/切割用設備配管

構造

內管層: 苯乙烯丁二烯合成橡膠配方

外管層: 耐磨耗, 耐候性佳之特殊橡膠, 可另為溝紋, 或紅色, 黃色

補強層: 適合夾合之纖維編織補強

適用溫度: -30 °C 到 +70°C

爆破壓力: 為最高使用壓力的4倍

產品編號 part no.	I.D. 內徑		braid 編織	O.D. 成品外徑		W.P. 最高使用壓力		Length 長度 M 公尺
	inch	mm		inch	mm	psi	kgf/cm ²	
OX 0152	3/16	4.8	2	0.492	12.5	250	18	100
OX 0202	1/4	6.3	2	0.570	14.5	250	18	100
OX 0252	5/16	7.9	2	0.649	16.5	250	18	100
OX 0302	3/8	9.5	2	0.708	18.0	250	18	100
OX 0151HP	3/16	4.8	1	0.452	11.5	350	25	100
OX 0201HP	1/4	6.3	1	0.511	13.0	350	25	100
OX 0251HP	5/16	7.9	1	0.590	15.0	350	25	100