

性能符號：◎優 ○良 □可 △劣

準特殊橡膠				特殊橡膠					
CSM	NBR	U	T	ACM	CO	ECO	Q	FKM	HNBR
1.15	0.98	1.16	0.34	1.10	1.36	1.27	0.98	1.82	0.98-1.00
30-115	30-100	25-60	25-50	45-60	35-120			35-160	
□	◎	△	×	△	△	△	○	△	◎
8.9	9.6	10.0	9.0	9.4	9.35	9.05	7.3	9.3	9.3-10.0
4/3/4/2	0/4/1/2	3/4/3/4	0/3/3/1	0/4/4/1	0/4/4/3		0/0/4/4	2/4/4/1	2/4/4/2
40-95	30-100	10-100	35-80	40-90	40-90		30-85	60-95	40-100
70-280	50-280	200-450	30-130	70-120	60-200		40-100	70-180	50-400
100-500	100-800	300-800	100-700	100-600	100-600		50-500	100-400	50-600
○	×	◎	×	×	×	×	×	○	◎
□	□	◎	△	△	△	○	◎	△	○
□	□	◎	×	×	○	○	×	△	○
□	○	◎	×	□	○	○	◎	◎	○
◎	◎	◎	×	△	△	□	×	○	◎
○	○	◎	×	○	○	○	□	○	○
150	130	90	80	180	150	140	230	260	170
-45	-45	-50	-40	-30	-30	-50	-90	-30	-65
◎	□-○	○	△	◎	○	○	◎	◎	◎
◎	×	◎	◎	◎	○	○	◎	◎	○
○	△	△	×	△	○	□	□	◎	△
○	○	○	◎	○	◎	○	×	◎	○
□	×	×	○	×	×	×	◎	△	×
□-○	◎	◎	◎	○	◎		□	◎	○
△	△	△	○	×	△		△	◎	△
○	◎	◎	◎	◎	◎		◎	◎	◎
×	×	□	□	×	□		□	○	×
△	×	△	○	×	×		△	△	×
×	△	×	○	×	×		○	◎	△
◎	□	×	□	×	□		○	△	○
△	×	×	◎	×	×		○	×	×
△	×	×	○	×	○		△	×	×
×	□	○	◎	×	○		×	×	○
□	□	×	×	×	□		○	◎	◎
△	△	×	○	×	×		○	□	○
◎	□	×	×	×	×		△	◎	○
◎	○	×	×	×	○		×	△	○
E	D	F	F	F	F		G	H	G
膠皮、內襯、耐侯塗料、膠管、皮帶、電線	油管、油封、滾筒、皮帶、薄片、襯條	實胎、皮帶、滾筒內襯、油封、O環、檔板	膠管、襯條、薄片、填縫、滾筒	膠管、襯條、油封耐油耐熱產品	耐油耐熱膠管、親條、O型環、薄片、耐油耐熱皮帶、滾筒		耐熱膠管、襯條、薄膜、O型環、耐熱電線、醫療用品	襯條O型環、薄片、耐油耐熱膠管	耐油、耐熱膠管、油封、O型環、橡膠滾筒、耐油耐熱皮帶